

# CHOISISSEZ VOTRE OPTIturn® TOUR

	Puissance	Hauteur de pointe	Centre pointes	Diamètre de tournage	Alésage de la broche	Vitesses de broche	Mandrin à 3 mors	Mandrin à 4 mors	Entraînement Vario	Affichage dig. de la vitesse	Version DPA	Éclairage	230V	400V
<b>TU1503V</b>	0,45	70	250	140	11	120-3000	●		●				●	
<b>TU2004V</b>	0,6	100	300	200	21	150-2500	●		●	●			●	
<b>TU2304</b>	0,75	115	450	230	20	125-2000	●						●	
<b>TU2304V</b>	0,75	115	450	230	20	150-2200	●		●	●			●	●
<b>TU2406</b>	0,75	125	550	250	21	125-2000	●						●	
<b>TU2406V</b>	1,1	125	550	250	21	150-2500	●						●	
<b>TU2506V</b>	1,1	125	550	250	26	150-2500	●		●	●			●	
<b>TU2807</b>	0,85	140	700	266	26	150-2000	●						●	●
<b>TU2807V</b>	1,5	140	700	266	26	30-4000	●		●	●			●	
<b>TU3008</b>	1,1	150	800	300	36	150-2000	●						●	
<b>TU3008V</b>	1,5	150	800	300	36	30-3000								
<b>TH3309/TH3309D</b>	1,5	156	910	350	38	60-2000					●/-	●		●
<b>TU3309V</b>	2,2	145	910	350	38	12-2250			●	●	●	●	●	
<b>TH3610/TH3610D</b>	1,5	180	1000	356	52	70-2000					●/-	●		●
<b>TH4010/TH4010D</b>	1,5/2,4	205	1000	410	52	45-1800					●/-	●		●
<b>TH4010V</b>	4	205	1000	410	52	30-3000			●	●	●	●		●
<b>D420x1000/1500</b>	4,5	210	1000/1500	420	52	45-1800	●	●			●	●		●
<b>TH4610/TH4615 TH4620</b>	5,5	230	1000/1500/2000	465	58	25-2000					●	●		●
<b>TH4615V</b>	7,5	230	1500	465	80	30-2000			●	●	●	●		●
<b>TH5615/TH5620 TH5630</b>	7,5	280	1500/2000/3000	560	80	25-1600					●	●		●
<b>TH5620V</b>	7,5	280	2000	560	105	25-1600			●	●	●	●		●
<b>D660x2000/3000</b>	7,5	330	2000/3000	660	105	25-1600	●	●			●	●		●
<b>TU8020/TU 8030</b>	7,5	330	2000/3000	660	105	25-1600	●				●	●		●